



## AMR-1 E Shock Absorbing Penetration Resistance Fragment Protection Protective Area Weight Anti Riot Helmet + Weight

Tech Specs	
Material	Fibre reinforced duroplast
Coating	2K- paint scratch & chemical resistance
Style	Full-Cut Anti Riot Shape
Edge Protection	EPDM rubber edge
Colours	black, olive green, midnight blue, white
Weight <sup>.</sup>	1350 g / 2.98 lbs with inside equipment, Neck Guard, Rails and Visor (3mm)
Shock Absorbtion	CPP-1 Pad System
Harness System	CRS-2 Harness System
Size	Unisize 52 - 62 cm / 6 ½ to 8
Interfaces	CRR-1 modular Railsystem

## Standards / Certifications

shock absorption according to EN 397, 5.1.1 resistance to penetration according to EN 397, 5.1.2 flame resistance according to EN 397, 5.1.3 lateral deformation according to E 397, 5.2.4

blunt impact resistance and resistance to penetration have been performed at -10°C (6.2.3), water immersion +20°C (6.2.5) and +50°C (6.2.4)

## **Special Properties | Accessories**

protection against penetration blunt impact protection heat-resistant helmet shell well ventilated pad system with air vents

3 mm (or thicker) visor with anti s**c**ratch and anti fog coating removable neck protection

CRR.1 (Riot Rail System) with fixed visor mount, gas mask and multi functional rail

additional accessories: flashlights, cameras, gas masks and helmet bags

