



## ARC-2 E Shock Absorbing Penetration Resistance Ballistic Protection Protective Area Weight Hallistic Anti Riot Helmet Hallistic Anti Riot Helmet Hallistic Anti Riot Helmet Hallistic Anti Riot Helmet Hallistic Anti Riot Helmet

Tech Specs	
Material	Kevlar Fiber
Coating	2K- paint scratch & chemical resistance
Style	Full-Cut Anti Riot Shape
Edge Protection	EPDM rubber edge
Colours	black, olive green, midnight blue, white
Weight*	1,98 kg / 4.36 lbs including inside equipment, Neck Guard, Rails and Visor (3mm)
Shock Absorbtion	CPP-1 R Pad System
Harness System	CRS-2 Harness System
Size	Unisize 52 - 62 cm / 6 <sup>1</sup> / <sub>2</sub> to 8
Interfaces	CRR-1 Railsystem

## Standards / Certifications

- ballistic protection against 9 mm rounds according to NIJ-STD-0106.01 IIIA, NIJ-STD-0108.01 (Chesapeake)
- STANAG 2920, 17 grain fragment: V50= 600+ m/s 1968+ fps
- shock absorption according to EN 397, 5.1.1
- resistance to penetration according to EN 397, 5.1.2
- flame resistance according to EN 397, 5.1.3
- lateral deformation according to E 397, 5.2.4
- shock absorption and resistance to penetration have been performed at -10°C (6.2.3), water immersion +20°C (6.2.5) and +50°C (6.2.4)

## **Special Properties | Accessories**

high level of protection against penetration
high level of blunt impact protection
heat-resistant helmet shell
good ventilation thanks pad system with air ducts

3 mm or thicker visor ( with anti s**c**ratch and anti fog coating removable neck protection

CRR.1 (Riot Rail System) with fixed visor mount, gas mask and multi functional rail

additional accessories: flashlights, cameras and gas masks

